

SCR243

PCMCIA Contact Smart Card Reader



Features

- ISO 7816 smart card reader
- PCMCIA type II slot
- Easy-to-install / remove
- Ideal for travellers due to its robust design
- Open-end mouth for convenient smart card insertion & removal
- In field firmware updates
- Compliant with all major smart cards and relevant industry standards
- Customization options: Company logo OEM branding on the label

Typical Applications

The SCR243 is ideal for the integration into notebooks, PDA's or PC bus systems with a standard PCMCIA Type II slot. It is suitable for a wide range of applications, e.g. home banking, network security, secure logon, email encryption, online gaming and shopping, as well as for online loyalty points redemption and other PC related applications.

Its robust metal-casing ensures highest durability in all conditions.

Contact Reader

Headquarters
SCM Microsystems GmbH
Oskar-Messter-Str. 13
85737 Ismaning, Germany
E-mail sales@scmmicro.com
Phone +49 89 9595 5000
Fax +49 89 9595 5555

U.S. Office
SCM Microsystems, Inc.
1900-B Carnegie Avenue
Santa Ana, CA 92705 USA
E-mail scmsales@scmmicro.com
Phone +1 888 446 9008
Fax +1 888 446 1210

SCM Microsystems Japan, Inc.
GoogolPlex Millennium Building 6F
4-4-20 Shiba, Minato-ku,
Tokyo, Japan 108-0014
E-mail sales@scmmicro.co.jp
Phone +81 3 6414 6611
Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd.
Module No. 0506, 0507 & 0508
D' Block South, 5th Floor
Tidel Park, 4 Canal Bank Road
Taramani
Chennai 600113, India
E-mail sales@scmmicro.co.in
Phone +91 44 2254 0020
Fax +91 44 2254 0029

www.scmmicro.com

SCR243

Technical Data

Interfaces		
Host	USB	<ul style="list-style-type: none"> • PC-Card 8 bits I/O 5V • PCMCIA Bus powered device • PCMCIA Type II
Smart Card	contact	<ul style="list-style-type: none"> • T=0, T=1 protocol support • Memory card support through SCM MCARD API • Communication speed up to 344,105 bps (PPS, FI parameter) • Frequency up to 8 MHz (PPS, DI parameter) • Support ISO 7816 Class A and AB smart card • 8 contacts - ISO location • 50,000 insertion/removal cycle • Friction contact
Software	API	<ul style="list-style-type: none"> • PC/SC • CT-API (thru wrapper on top of PC/SC)
Operating Systems		
		<ul style="list-style-type: none"> • Windows® 7 • Windows® Vista, XP, Server2003, 2000, NT4, ME, 98 • Windows® Vista, XP, Server2003 (AMD64/EMT64) • Windows® CE 3.0, 4.2, 5.0 • MacOS X • Linux 32-bit (2.4.x, 2.6.x)
Connector		
		• 68 pins PCMCIA connector
Dimensions		L x W x H [mm]
		• 85.6 x 54 x 5
Weight		[g]
		• 30
Operating Conditions		Temperature [°C] Humidity [%]
		<ul style="list-style-type: none"> • 0 to 50 • 90 (non-condensing)
Approvals		Functional
		<ul style="list-style-type: none"> • FCC Class B part 15, cULus, CE, VCCI, ANZI, CNS • EMV 2000 Level 1 • Microsoft® WHQL 2000, XP, Server2003
		Environmental
		• RoHS, WEEE

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

Trusted Partner

- ASIC (application specific IC) and smart card reader development experience since 1990
- Innovative solutions - more than 50 patents filed
- Reliable high-quality mass production capability - more than 15 Mio. reader solutions deployed to date
- Active role in standardization committees
- Complex project management expertise e.g. U.S. Department of Defense CAC program, electronic ID applications (ePassport, health card projects, national ID, driver licence)

Support

- Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

Trusted Products

- Broadest portfolio of security technology products - for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design - certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions - SCM's SmartOS™ firmware and its own ASIC technology allow in Field upgrades and secure your investment

